



Specification	
<b>Model</b>	DE7000
<b>Housing Material:</b>	SECC t=0.8mm
<b>Housing Color:</b>	Black
<b>Form Factor:</b>	AOpen Form Factor
<b>Dimension:</b>	166(W) x 48(H) x 164.1(D) mm 6.54(W) x 1.89(H) x 6.46(D) inch
<b>Volume:</b>	1.30L
<b>Weight(Kg/Pound) :</b>	1.2 kg / 2.64 pound (N.W.)
<b>CPU:</b>	Support Intel Core 2 Duo, Celeron Mobile CPU (Penryn & Santa Rosa Refresh) TDP≤35W Socket P FSB 667/800/1066MHz
<b>Chipset:</b>	Nvidia MCP7A-LP Chipset
<b>Memory:</b>	Dual Channel Mode DDR3 SO-DIMM x 2 800/1066/1333 <b>Max memory size : 4GB*</b>
<b>Graphics:</b>	GeForce 9300 <b>DVI Port : N/A</b> <b>VGA Port : x 1</b> <b>HDMI Port : x 1</b> <b>Multi-TV Out Port : N/A</b>
<b>Expansion Slot:</b>	<b>mini Card Slot : Optional</b> <b>mini PCI Slot : N/A</b>
<b>Audio:</b>	Realtek ALC662 HD Audio CODEC on-board Stereo / 5.1 CH with HDMI
<b>LAN:</b>	Realtek Gigabit Ethernet/ 10/100/1000
<b>USB:</b>	x 6 (4 (Rear), 2 (Front)) Integrated in chipset
<b>IEEE 1394:</b>	N/A
<b>Storage:</b>	<b>ATA Connector : x 1</b> (for Slim Optical) <b>S-ATA Connector : x 1</b> (for 2.5" HDD)
<b>Storage Bay:</b>	<b>Slot-in Slim ODD Bay : x 1</b> <b>2.5" SATA II HDD Bay : x 1</b> <b>CF card socket : N/A</b>
<b>Chassis:</b>	Slot-in Slim ODD Bay x 1 2.5" SATA II HDD Bay x 1
<b>Front Panel IO:</b>	USB 2.0 Port x 2 Power Button x 1 HDD indicator (Blue) x 1 Power indicator (Blue) x 1
<b>Rear Panel IO:</b>	<b>DC in Jack : x 1</b> <b>DVI Port : N/A</b> <b>VGA Port : x 1</b> <b>HDMI Port : x 1</b> <b>S-Video Out Port : N/A</b> <b>USB 2.0 Port : x 4</b> (Rear) <b>IEEE 1394 Port : N/A</b> <b>RJ-45 LAN Jack : x 1</b> <b>Legacy RS232 Serial Port (COM Port) : RS232 Serial Port x 1</b> <b>PS/2 Port : N/A</b>



	<b>Audio Set Line-In</b> : x 1 <b>Audio Set Line-Out</b> : x 1 <b>Audio Set Mic-In</b> : x 1 <b>Upgrade for Antenna Port</b> : x 2 <b>Kensington Lock Hole</b> : x 1 <b>Audio I/O Ports</b> : 5.1 channel Audio I/O Ports x 1 (Line-In, Line-Out, Mic-In)
<b>Security:</b>	N/A <b>Kensington Lock Hole</b> : x 1 (Rear)
<b>CPU Thermal:</b>	<b>Module</b> : AOpen Thermal Module <b>Noise</b> : 27dB
<b>WatchDog Timer:</b>	1 ~ 255 sec/min
<b>Adapter:</b>	90W (20V, 4.5A) AC Adapter
<b>Input Voltage:</b>	AC 100 ~ 240V
<b>Environment:</b>	<b>MTBF</b> : 40,000 hrs <b>Operating Temperature</b> : 0 ~ 50°C (32 ~ 122°F) <b>Storage Temperature</b> : -30 ~ 60°C (-22 ~ 140°F) <b>Relative Humidity</b> : 90% RH (45°C non-Condensing) <b>Operating Vibration</b> : 0.5Grms, Random, 10~500Hz, X,Y,Z 3Axes, 0.5hr/Axis <b>Non-Operating Vibration</b> : 2Grms, random, 10~300Hz, X,Y,Z 3Axes, 1hr/Axis <b>Operating Shock</b> : 8G, half sine, 11ms duration, X,Y,Z 3Axes, 6Direction, 3 shocks/direction <b>Non-Operating Shock</b> : 50G, Half sine, 11ms duration
<b>Accessory:</b>	Please check out your local dealer. <b>Optional</b> : Please check out our "Accessories" for detail
<b>Certification:</b>	CE, FCC, UL, CB
<b>Support OS:</b>	Windows Vista Premium / Basic, Windows XP, Windows Embedded, Windows 7

